

NEOPAINT NPT16 – AEROSOL

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2020/878

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name NEOPAINT NPT16 – AEROSOL

Unique Formula Identifier (UFI) T300-D0AK-J00W-2FCT

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) White Background Paint for use in the Magnetic Particle Inspection Process (BS EN ISO 9934-2:2002).

Uses Advised Against None known.

1.3 Details of the supplier of the safety data sheet

Manufacturer

Company Identification Johnson and Allen Ltd

Address of Manufacturer Neocol Works

Smithfield

Sheffield

Postal code S3 7AR

Telephone 0114 2738066

Fax 0114 2729842

E-mail info@johnsonandallen.co.uk

Office hours 08:30 - 17:00

Only representative

Company Identification DIMART S.r.l.

Address Via A. Einstein

13 Sedriano MI

Italy

Postal code 20018

Telephone +390290310207

Fax +390290310208

1.4 Emergency telephone number

Company 0114 2738066 (UK office hours 08.30-17.00)

NHS Direct +44 111

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008 (CLP) Aerosol 3 :Pressurised container: May burst if heated.

Skin Irrit. 2 :Causes skin irritation.

Eye Irrit. 2 :Causes serious eye irritation.

STOT SE 3 :May cause drowsiness or dizziness.

Carc. 2 :Suspected of causing cancer.

2.2 Label elements

According to Regulation (EC) No. 1272/2008 (CLP)

Product Name NEOPAINT NPT16 – AEROSOL

NEOPAINT NPT16 – AEROSOL

Hazard Pictogram(s)



GHS08



GHS07

Signal Word(s)

Warning

Hazard Statement(s)

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer.

Precautionary Statement(s)

P201: Obtain special instructions before use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Unique Formula Identifier (UFI)

T300-D0AK-J00W-2FCT

2.3 Other hazards

None.

2.4 Additional Information

For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product as supplied: Aerosol.

3.1 Substances

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / REACH Registration No.	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Dichloromethane	75-09-2	200-838-9 / 01-2119480404-41-XXXX	60-70	Skin Irrit. 2 H315 Eye Irrit. 2 H319 STOT SE 3 H336 Carc. 2 H351	GHS08 GHS07
Carbon dioxide	124-38-9	204-696-9	10-20	Press. Gas (Comp.) H280	GHS04
Xylene	1330-20-7	215-535-7 / 01-2119488216-32-XXXX	1-10	Flam. Liq. 3 H226 Acute Tox. 4 H312 Skin Irrit. 2 H315 Acute Tox. 4 H332	GHS02 GHS07
Ethylbenzene	100-41-4	202-849-4 / 01-2119489370-35-XXXX	<2	Flam. Liq. 2 H225 Asp. Tox. 1 H304	GHS02 GHS08

NEOPAINT NPT16 – AEROSOL

				Acute Tox. 4 H332 STOT RE 2 H373	GHS07
--	--	--	--	-------------------------------------	-------

HAZARDOUS INGREDIENT(S)	CAS No.	Specific Concentration Limit	M-factor	ATE
Xylene	1330-20-7			Acute Tox. 4 (H312): 1100.000 Acute Tox. 4 (H332): 1.500
Ethylbenzene	100-41-4			Acute Tox. 4 (H332): 1.500

Contains no non-classified vPvB substances.

Contains no non-classified substances with a Union workplace exposure limit.

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
Skin Contact	Take off contaminated clothing and wash it before reuse. Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Unlikely route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness.
Suspected of causing cancer.

4.3 Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get medical advice/attention.

SECTION 5: FIREFIGHTING MEASURES

Pressurised container: May burst if heated.

5.1 Extinguishing media

Suitable Extinguishing media	As appropriate for surrounding fire.
Unsuitable extinguishing media	None known.

5.2 Special hazards arising from the substance or mixture

Heating may cause pressure rise with risk of bursting. Decomposes in a fire giving off toxic fumes: Phosgene, Hydrogen chloride, Carbon monoxide, Carbon dioxide.

5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions. Keep containers cool by spraying with water if exposed to fire.

NEOPAINT NPT16 – AEROSOL

SECTION 6: ACCIDENTAL RELEASE MEASURES

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

6.1 Personal precautions, protective equipment and emergency procedures

Stop leak if safe to do so. Provide adequate ventilation. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Ensure full personal protection (including respiratory protection) during removal of spillages.

6.2 Environmental precautions

Do not release large quantities into the surface water or into drains.

6.3 Methods and material for containment and cleaning up

Collect mechanically and dispose of according to Section 13. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a lidded container for disposal or recovery. Containers must not be punctured or destroyed by burning, even when empty.

6.4 Reference to other sections

See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurised container - Do not pierce or burn, even after use. Provide adequate ventilation. Use only outdoors or in a well-ventilated area. Avoid breathing mist/vapours/spray. Avoid contact with skin and eyes. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands and exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Protect from sunlight. Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Storage temperature

Do not expose to temperatures exceeding 50°C/ 122°F.

Storage life

Stable under normal conditions.

Incompatible materials

Strong oxidising agents, Alkalies, Zinc, Aluminium.

7.3 Specific end use(s)

White Background Paint for use in the Magnetic Particle Inspection Process (BS EN ISO 9934-2:2002).

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

NEOPAINT NPT16 – AEROSOL

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
Dichloromethane	75-09-2	100	353	200	706	BMGV, Sk
Carbon dioxide	124-38-9	5000	9150	15000	27400	
Xylene, o-,m-,p- or mixed isomers	1330-20-7	50	220	100	441	Sk, BMGV
Ethylbenzene	100-41-4	100	441	125	552	Sk

Region Source
United Kingdom UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark Notes
BMGV Biological monitoring guidance values are listed in Table 2.
Sk Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

Biological Exposure Indices						
Substances	CAS Number	Sampling	Tissues	Control parameters	Biological monitoring guidance value	Comments
Dichloromethane	75-09-2	Post shift	end-tidal breath	carbon monoxide	30 ppm	
Xylene, o-, m-, p- or mixed isomers	1330-20-7	Post shift	urine	methyl hippuric acid	650 mmol methyl hippuric acid/mol creatinine	

8.2 Exposure controls

8.2.1. Appropriate engineering controls Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Use with ventilation, local exhaust ventilation or breathing protection. A washing facility/water for eye and skin cleaning purposes should be present.

8.2.2. Personal protection equipment



Eye Protection

Wear eye protection with side protection (EN166).



Skin protection

Wear suitable protective clothing and gloves. Impervious gloves (EN 374).
Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Protective gloves should be replaced at first signs of wear.
Material: Fluorinated Rubber (Viton)
Break through time: > 480 min
Glove thickness: > 0.4 mm

NEOPAINT NPT16 – AEROSOL

Material: PVA
Break through time: > 480 min
Glove thickness: > 0.4 mm
Material: Butyl Rubber
Break through time: > 10 min
Glove thickness: > 0.4 mm



Respiratory protection

A Wear a suitable respirator to keep the solvent vapour concentration below the occupational limit values. A suitable mask with filter type AX is appropriate.



Thermal hazards

Not applicable.

8.2.3. Environmental Exposure Controls Do not release large quantities into the surface water or into drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state	Aerosol
Colour	White.
Odour	Characteristic odour.
Melting point/freezing point	-94.9°C (Dichloromethane)
Boiling point or initial boiling point and boiling range	39.8°C (Dichloromethane)
Flammability	Non-flammable.
Lower and upper explosion limit	Not known.
Flash Point	Not applicable.
Auto-ignition temperature	Not known.
Decomposition Temperature	Not known.
pH	Not known.
Kinematic Viscosity	Not known.
Solubility	Solubility (Water) : Insoluble in water. Solubility (Other) : Not known.
Partition coefficient n-octanol/water (log value)	1.25 (Dichloromethane)
Vapour pressure	584 hPa (352 mm Hg) @ 25°C (Dichloromethane)
Density and/or relative density	Density: 1.32 g/cm ³ @ 25°C (Dichloromethane)
Relative vapour density	Not known.
Particle characteristics	Not known.

9.2 Other information

Explosive properties Pressurised container: May burst if heated.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Stable under normal conditions.

10.2 Chemical Stability

NEOPAINT NPT16 – AEROSOL

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Keep away from heat and direct sunlight.

10.5 Incompatible materials

Strong oxidising agents, Alkalis, Zinc, Aluminium.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Ingestion

Calculation method : Not classified.

Low oral toxicity.

Dichloromethane: LD50 (rat) > 2000 mg/kg

Acute toxicity - Skin Contact

Calculation method : Not classified.

Low acute toxicity.

Dichloromethane: LD50 (rat) > 2000 mg/kg

Acute toxicity - Inhalation

Calculation method : Not classified.

Low acute toxicity.

Dichloromethane: LC50 (rat) (4 hours) = 49 mg/l

Skin corrosion/irritation

Calculation method : Causes skin irritation. No data.

Serious eye damage/irritation

Calculation method : Causes serious eye irritation. No data.

Skin sensitization data

Calculation method : Not classified.

It is not a skin sensitiser.

Respiratory sensitization data

Calculation method : Not classified.

Germ cell mutagenicity

Calculation method : Not classified.

There is no evidence of mutagenic potential.

Carcinogenicity

Calculation method : Suspected of causing cancer. No data.

Dichloromethane:

A3: Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histological type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiological studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure.

Reproductive toxicity

Calculation method : Not classified.

No evidence of reproductive effects.

Lactation

Calculation method : Not classified.

STOT - single exposure

Calculation method : May cause drowsiness or dizziness. No data.

STOT - repeated exposure

Calculation method : Not classified.

Aspiration hazard

Calculation method : Not classified.

11.2 Information on other hazards

None.

NEOPAINT NPT16 – AEROSOL

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity - Aquatic invertebrates	Low toxicity to invertebrates.
Toxicity - Fish	Low toxicity to fish. Dichloromethane: LC50 (96 hour) = 193 mg/l
Toxicity - Algae	Low toxicity to algae.
Toxicity - Sediment Compartment	Not classified.
Toxicity - Terrestrial Compartment	Not classified.

12.2 Persistence and degradability

The product is biodegradable. The product is unlikely to persist in the environment.

12.3 Bioaccumulative potential

The product has no potential for bioaccumulation.

Dichloromethane: Bioconcentration factor (BCF): 2.0-5.4

12.4 Mobility in soil

The product is volatile and will partition into the atmosphere. The product has high mobility in soil.

12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

12.6 Endocrine disrupting properties

None known.

12.7 Other adverse effects

None.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Non-emptied aerosol: Dispose of wastes in an approved waste disposal facility.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number

UN No. 1950

14.2 UN proper shipping name

UN proper shipping name AEROSOLS

14.3 Transport hazard class(es)

ADR/RID

ADR/RID Class 2

ADR Classification Code 5A

Special Provisions 190, 327, 344, 625

Limited Quantities 1 L

NEOPAINT NPT16 – AEROSOL

Excepted Quantities	E0
Emergency Action Code	
Mixed Packing Instructions for Packages	P207 LP200
Special Packing Provisions for Packages	PP87 RR6 L2
Mixed Packing Instructions for Packages	MP9
Packing Instructions for Portable Tanks	
Special Provisions for Portable Tanks	
Tank Code for Tanks	
Special Provisions for Tanks	
Vehicle for Tank Carriage	
ADR Transport Category	3
Tunnel Restriction Code	E
Special Provisions for Carriage - Packages	V14
Special Provisions for Carriage - Bulk	
Special Provisions for Carriage - Loading, Unloading and Handling	CV9 CV12
Special Provisions for Carriage - Operation	
ADR HIN	
IMDG	
IMDG Class	2
Special Provisions	190, 327, 344, 625
Limited Quantities	1 L
Excepted Quantities	E0
Mixed Packing Instructions for Packages	P207 LP200
Special Packing Provisions for Packages	PP87 RR6 L2
Packing Instructions for Portable Tanks	
Special Provisions for Portable Tanks	
IMDG EMS	F-D, S-U
Stowage and Handling	SW1 SW22
Segregation	SG69
Marine Pollutant	
ICAO/IATA	
IATA Proper Shipping Name	AEROSOLS
Excepted Quantities	E0
Passenger and Cargo Aircraft Limited Quantities Packing Instructions	Y203
Passenger and Cargo Aircraft Limited Quantities Max net Qty	30Kg
Passenger and Cargo Aircraft Packing Instructions	203
Passenger and Cargo Aircraft Max net	75Kg

NEOPAINT NPT16 – AEROSOL

Qty
 Cargo Aircraft Packing Instructions 203
 Cargo Aircraft Max net Qty 150Kg
 Special Provisions A98, A145, A167, A802
 Emergency Response Guidebook (ERG) 2L
 Code
 Labels
 Labels 2.2



14.4 Packing group

Packing group

14.5 Environmental hazards

Environmental hazards Not classified as a Marine Pollutant.

14.6 Special precautions for user

Special precautions for user Not known.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No information available

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Regulations - Authorisations and/or Restrictions On Use

Candidate List of Substances of Very Not listed

High Concern for Authorisation

REACH: ANNEX XIV list of substances Not listed

subject to authorisation

REACH: Annex XVII Restrictions on the Dichloromethane (75-09-2), Xylene (1330-20-7), Ethylbenzene (100-41-4)

manufacture, placing on the market and

use of certain dangerous substances,

mixtures and articles

Community Rolling Action Plan (CoRAP) Dichloromethane (75-09-2), Xylene (1330-20-7)

Regulation (EU) N° 2019/1021 of the Not listed

European Parliament and of the Council

on persistent organic pollutants

Regulation (EC) N° 1005/2009 on Not listed

substances that deplete the ozone layer

Regulation (EU) N° 649/2012 of the Not listed

European Parliament and of the Council

concerning the export and import of

hazardous chemicals

National regulations

Other Not known.

15.2 Chemical Safety Assessment

NEOPAINT NPT16 – AEROSOL

Not applicable.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

1, 2

LEGEND

Hazard Pictogram(s)



GHS08



GHS07

GHS02: GHS: Flame

GHS04: GHS: Gas cylinder

Hazard classification

Flam. Liq. 2 : Flammable liquid, Category 2

Flam. Liq. 3 : Flammable liquid, Category 3

Aerosol 3 : Aerosol, Category 3

Press. Gas (Comp.) : Gases under pressure, Compressed gas

Asp. Tox. 1 : Aspiration hazard, Category 1

Acute Tox. 4 : Acute toxicity, Category 4

Skin Irrit. 2 : Skin corrosion/irritation, Category 2

Eye Irrit. 2 : Serious eye damage/irritation, Category 2

Acute Tox. 4 : Acute toxicity, Category 4

STOT SE 3 : Specific target organ toxicity — single exposure, Category 3

Carc. 2 : Carcinogenicity, Category 2

STOT RE 2 : Specific target organ toxicity — repeated exposure, Category 2

Hazard Statement(s)

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement(s)

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

NEOPAINT NPT16 – AEROSOL

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P312: Call a POISON CENTRE/doctor if you feel unwell.

P321: Specific treatment (see Medical Advice on this label).

P332+P313: If skin irritation occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

P501: Dispose of contents in accordance with local, state or national legislation.

Acronyms

ADN : European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate

CAS : Chemical Abstracts Service

CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

DNEL : Derived No Effect Level

EC : European Community

EINECS : European Inventory of Existing Commercial Chemical Substances

IATA : International Air Transport Association

IBC : Intermediate Bulk Container

ICAO : International Civil Aviation Organization

IMDG : International Maritime Dangerous Goods

LTEL : Long term exposure limit

PBT : Persistent, Bioaccumulative and Toxic

PNEC : Predicted No Effect Concentration

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

NEOPAINT NPT16 – AEROSOL

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL : Short term exposure limit

STOT : Specific Target Organ Toxicity

UN : United Nations

vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for data used to compile the SDS Regulation (EC) No. 1272/2008 (CLP)

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose.

Johnson and Allen Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Johnson and Allen Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.