

NEOPAINT 2 - BULK

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 and SI 2020/1577

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name NEOPAINT 2 - BULK

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) For use in the Magnetic Particle Inspection Process (BS EN ISO 9934-2:2002).

Uses Advised Against Not known.

1.3 Details of the supplier of the safety data sheet

Company Identification Johnson and Allen Ltd
Address of Supplier Neocol Works
Smithfield
Sheffield
Postal code S3 7AR
Telephone 0114 2738066
Fax 0114 2729842
E-mail info@johnsonandallen.co.uk
Office hours 08:30 - 17:00

1.4 Emergency telephone number

Company 0114 2738066 (UK office hours 08.30-17.00)
NHS Direct +44 111

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567
Flam. Liq. 2 :Highly flammable liquid and vapour.
Skin Irrit. 2 :Causes skin irritation.
Eye Irrit. 2 :Causes serious eye irritation.
STOT SE 3 :May cause drowsiness or dizziness.

2.2 Label elements

Product Name NEOPAINT 2 - BULK
Hazard Pictogram(s) According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567



GHS02



GHS07

Signal Word(s) Danger

Hazard Statement(s) H225: Highly flammable liquid and vapour.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

Precautionary Statement(s) EUH066: Repeated exposure may cause skin dryness or cracking.
P240: Ground and bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting/equipment.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233: Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

None known.

2.4 Additional Information

For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / Registration number(s)	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Acetone	67-64-1	200-662-2	60-100	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336 EUH066	GHS02 GHS07

NEOPAINT 2 - BULK

Xylene	1330-20-7	215-535-7	5-10	Flam. Liq. 3 H226 Acute Tox. 4 H312 Skin Irrit. 2 H315 Acute Tox. 4 H332	GHS02 GHS07
--------	-----------	-----------	------	---	----------------

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures**

Inhalation	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
Skin Contact	Wash with plenty of water. Take off immediately all contaminated clothing. Do not use solvents or diluting agents for skin cleaning. If skin irritation occurs: Get medical advice/attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Wash out mouth with water. Do not give anything by mouth to an unconscious person. If symptoms persist, obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Unlikely to be required but if necessary treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Highly flammable liquid and vapour.

5.1 Extinguishing media

Suitable Extinguishing media	Use water spray, foam, dry powder or CO ₂ to extinguish.
Unsuitable extinguishing media	Water jet spray.

5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapour. Decomposes in a fire giving off toxic fumes: Carbon monoxide, Carbon dioxide, Nitrogen oxides. Vapours or fumes: Can form explosive mixture with air.

5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Eliminate all ignition sources if safe to do so. Avoid breathing vapours. Avoid contact with skin and eyes. Wear protective gloves/eye protection. Wash hands thoroughly after handling.

6.2 Environmental precautions

Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Absorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Containers must not be punctured or destroyed by burning, even when empty. Wash the spillage area with water.

6.4 Reference to other sections

See Also Section 8, 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use non-sparking tools. Take action to prevent static discharges. Provide adequate ventilation. Use only outdoors or in a well-ventilated area. Avoid breathing vapours. Avoid contact with skin and eyes. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands and exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Storage temperature	< 25°C
Special storage conditions	The storage of this product is subject to the requirements of the Highly Flammable and Liquid Petroleum Gases Regulations.

NEOPAINT 2 - BULK

Storage life
Incompatible materials
7.3 Specific end use(s)

Stable under normal conditions.
Oxidizing agents, Strongly acidic, Strongly alkaline.

For use in the Magnetic Particle Inspection Process (BS EN ISO 9934-2:2002).

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****8.1.1 Occupational Exposure Limits**

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Acetone	67-64-1	500	1210	1500	3620	
Xylene, o-,m-,p- or mixed isomers	1330-20-7	50	220	100	441	Sk, BMGV

Region United Kingdom
Source UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark Sk
Notes Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.
BMGV Biological monitoring guidance values are listed in Table 2.

Biological Exposure Indices						
Substances	CAS Number	Sampling	Tissues	Control parameters	Biological monitoring guidance value	Comments
Xylene, o-, m-, p- or mixed isomers	1330-20-7	Post shift	urine	methyl hippuric acid	650 mmol methyl hippuric acid/mol creatinine	

8.2 Exposure controls

8.2.1. Appropriate engineering controls Provide adequate ventilation, including appropriate local extraction, to ensure that the occupational exposure limit is not exceeded. A washing facility/water for eye and skin cleaning purposes should be present.

8.2.2. Personal protection equipment

Eye Protection Wear eye protection with side protection (EN166).



Skin protection Wear protective clothing and gloves: Impervious gloves (EN 374).
Recommended: Butyl rubber.
Glove thickness: ≥ 0.5 mm
Break through time: > 480 minutes.



Respiratory protection Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. A suitable mask with filter type AX may be appropriate.



Thermal hazards Not applicable.

8.2.3. Environmental Exposure Controls Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

Appearance Liquid.
Colour: White.
Odour Characteristic.
Odour threshold Not established.
pH Not known.
Melting point/freezing point -95.4°C (Acetone)
Initial boiling point and boiling range 56.2°C @ 1013 hPa (Acetone)
Flash Point < 21°C
Evaporation rate Not known.
Flammability (solid, gas) Not applicable.

NEOPAINT 2 - BULK

Upper/lower flammability or explosive limits	Not known.
Vapour pressure	233 hPa @ 20°C (Acetone)
Vapour density	Not known.
Density (g/ml)	Not known.
Relative density	0.95-1
Solubility(ies)	Solubility (Water): Immiscible with water. Solubility (Other): Not known.
Partition coefficient: n-octanol/water	Not known.
Auto-ignition temperature	465°C @ 1013 hPa (Acetone)
Decomposition Temperature (°C)	Not known.
Viscosity	Not known.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2 Other information	
Volatile Organic Compound Content	713 g/l

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Stable under normal conditions.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Vapours or fumes: Can form explosive mixture with air.

10.4 Conditions to avoid

Avoid friction, sparks, or other means of ignition.

10.5 Incompatible materials

Oxidizing agents, Strongly acidic, Strongly alkaline.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity - Ingestion	Calculation method : Not classified. Low oral toxicity.
Acute toxicity - Skin Contact	Acetone: LD50 (rat) = 5800 mg/kg Calculation method : Not classified. Low acute toxicity.
Acute toxicity - Inhalation	Acetone: LD50 (rabbit) > 7400 mg/kg Calculation method : Not classified. Low acute toxicity.
Skin corrosion/irritation	Acetone: LC50 (rat) = 132 mg/l Calculation method : Causes skin irritation. No data. Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation	Calculation method : Causes serious eye irritation. No data.
Skin sensitization data	Calculation method : Not classified. It is not a skin sensitizer.
Respiratory sensitization data	Calculation method : Not classified.
Germ cell mutagenicity	Calculation method : Not classified. There is no evidence of mutagenic potential.
Carcinogenicity	Calculation method : Not classified. No evidence of carcinogenicity.
Reproductive toxicity	Calculation method : Not classified. No evidence of reproductive effects.
Lactation	Calculation method : Not classified.
STOT - single exposure	Calculation method : May cause drowsiness or dizziness. No data.
STOT - repeated exposure	Calculation method : Not classified.
Aspiration hazard	Calculation method : Not classified.

11.2 Other information

Not known.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Low toxicity to aquatic organisms.

12.2 Persistence and degradability

The product is biodegradable. Unlikely to persist.

12.3 Bioaccumulative potential

The product has no potential for bioaccumulation.

NEOPAINT 2 - BULK

12.4 Mobility in soil

Immiscible with water. The product is predicted to have moderate mobility in soil. The vapour is heavier than air and spreads along ground.

12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

12.6 Other adverse effects

Not known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Dispose of contents/container to: Licensed recycler. Refer to manufacturer or supplier for information on recovery or recycling. Do NOT landfill.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number

UN No. 1263

14.2 UN proper shipping name

UN proper shipping name PAINT (vapour pressure at 50 °C not more than 110 kPa)

14.3 Transport hazard class(es)

ADR/RID

ADR/RID Class 3

ADR Classification Code F1

Special Provisions 163, 367, 640D, 650

Limited Quantities 5 L

Excepted Quantities E2

Emergency Action Code •3YE

Mixed Packing Instructions for Packages P001 IBC02 R001

Special Packing Provisions for Packages PP1

Mixed Packing Instructions for Packages MP19

Packing Instructions for Portable Tanks T4

Special Provisions for Portable Tanks TP1 TP8 TP28

Tank Code for Tanks LGBF

Special Provisions for Tanks

Vehicle for Tank Carriage FL

ADR Transport Category 2

Tunnel Restriction Code D/E

Special Provisions for Carriage - Packages

Special Provisions for Carriage - Bulk

Special Provisions for Carriage - Loading, Unloading and Handling

Special Provisions for Carriage - Operation S2 S20

ADR HIN 33

IMDG

IMDG Class 3

Special Provisions 163, 367, 640D, 650

Limited Quantities 5 L

Excepted Quantities E2

Mixed Packing Instructions for Packages P001 IBC02 R001

Special Packing Provisions for Packages PP1

Packing Instructions for Portable Tanks T4

Special Provisions for Portable Tanks TP1 TP8 TP28

IMDG EMS F-E, S-E

Stowage and Handling Category B

Segregation

Marine Pollutant

ICAO/IATA

IATA Proper Shipping Name PAINT (vapour pressure at 50 °C not more than 110 kPa)

Excepted Quantities E2

Passenger and Cargo Aircraft Limited Quantities Packing Instructions Y341

Passenger and Cargo Aircraft Limited Quantities Max net Qty 1L

Passenger and Cargo Aircraft Limited Quantities Max net Qty

NEOPAINT 2 - BULK

Passenger and Cargo Aircraft Packing Instructions	353
Passenger and Cargo Aircraft Max net Qty	5L
Cargo Aircraft Packing Instructions	364
Cargo Aircraft Max net Qty	60L
Special Provisions	A3, A72, A192
Emergency Response Guidebook (ERG) Code	3L
Labels	
Labels	3



14.4 Packing group

Packing group II

14.5 Environmental hazards

Environmental hazards Not classified as a Marine Pollutant.

14.6 Special precautions for user

Special precautions for user Not known.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No information available

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

United Kingdom Regulations - Authorisations and/or Restrictions On Use	
UK REACH Candidate List of Substances Not listed of Very High Concern for Authorisation	
UK REACH Authorisation List (Annex XIV) list of substances subject to authorisation	Not listed
UK REACH Restrictions List (Annex XVII) Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Acetone (67-64-1), Xylene (1330-20-7)
UK REACH Rolling Action Plan (RAP)	Not listed
The Persistent Organic Pollutants Regulations 2007 (SI 2007/3106) as amended	Not listed
The Ozone-Depleting Substances and Fluorinated Greenhouse Gases (Amendment etc.) (EU Exit) Regulations 2019 (SI 2019/583)	Not listed
The Prior Informed Consent (PIC) Regulations concerning the export and import of hazardous chemicals SI2008/2108 as amended	Not listed
European Regulations - Authorisations and/or Restrictions On Use	
Community Rolling Action Plan (CoRAP)	Xylene (1330-20-7)
15.2 Chemical Safety Assessment	
United Kingdom	Not applicable.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16

LEGEND

Hazard Pictogram(s)



GHS02



GHS07

Hazard classification

Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3

NEOPAINT 2 - BULK

Hazard Statement(s)	<p>Acute Tox. 4 : Acute toxicity, Category 4 Skin Irrit. 2 : Skin corrosion/irritation, Category 2 Eye Irrit. 2 : Serious eye damage/irritation, Category 2 Acute Tox. 4 : Acute toxicity, Category 4 STOT SE 3 : Specific target organ toxicity — single exposure, Category 3 H225: Highly flammable liquid and vapour. H226: Flammable liquid and vapour. H312: Harmful in contact with skin. H315: Causes skin irritation. H319: Causes serious eye irritation. H332: Harmful if inhaled. H336: May cause drowsiness or dizziness. EUH066: Repeated exposure may cause skin dryness or cracking.</p>
Precautionary Statement(s)	<p>P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233: Keep container tightly closed. P240: Ground and bond container and receiving equipment. P241: Use explosion-proof electrical/ventilating/lighting/equipment. P242: Use non-sparking tools. P243: Take action to prevent static discharges. P261: Avoid breathing vapours. P264: Wash hands and exposed skin thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection. P302+P352: IF ON SKIN: Wash with plenty of water. P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312: Call a POISON CENTRE/doctor if you feel unwell. P332+P313: If skin irritation occurs: Get medical advice/attention. P337+P313: If eye irritation persists: Get medical advice/attention. P362+P364: Take off contaminated clothing and wash it before reuse. P370+P378: In case of fire: Use water spray, foam, dry powder or CO₂ to extinguish. P403+P233: Store in a well-ventilated place. Keep container tightly closed. P403+P235: Store in a well-ventilated place. Keep cool. P405: Store locked up. P501: Dispose of contents/container to: Licensed recycler.</p>
Acronyms	<p>ADN : European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road ATE : Acute Toxicity Estimate CAS : Chemical Abstracts Service DNEL : Derived No Effect Level EC : European Community EINECS : European Inventory of Existing Commercial Chemical Substances IATA : International Air Transport Association IBC : Intermediate Bulk Container ICAO : International Civil Aviation Organization IMDG : International Maritime Dangerous Goods LTEL : Long term exposure limit PBT : Persistent, Bioaccumulative and Toxic PNEC : Predicted No Effect Concentration REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals RID : Regulations concerning the International Carriage of Dangerous Goods by Rail STEL : Short term exposure limit STOT : Specific Target Organ Toxicity UN : United Nations vPvB : very Persistent and very Bioaccumulative</p>

NEOPAINT 2 - BULK

Key literature references and sources for GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567
data used to compile the SDS
Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose.

Johnson and Allen Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law.

Johnson and Allen Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.