

## NEOPAINT NPT16 - AEROSOL

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 and SI 2020/1577

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Product Name NEOPAINT NPT16 - AEROSOL

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) White Background Paint for use in the Magnetic Particle Inspection Process (BS EN ISO 9934-2:2002).

Uses Advised Against Not known.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer

Company Identification Johnson and Allen Ltd

Address of Manufacturer Neocol Works

Smithfield

Sheffield

Postal code S3 7AR

Telephone 0114 2738066

Fax 0114 2729842

E-mail info@johnsonandallen.co.uk

Office hours 08:30 - 17:00

Only representative

Company Identification DIMART S.r.l.

Address Via A. Einstein

13 Sedriano MI

Italy

Postal code 20018

Telephone +390290310207

Fax +390290310208

#### 1.4 Emergency telephone number

Company 0114 2738066 (UK office hours 08.30-17.00)

NHS Direct +44 111

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

GB CLP Regulation, UK SI 2019/720 and Aerosol 3 :Pressurised container: May burst if heated.

UK SI 2020/1567 Skin Irrit. 2 :Causes skin irritation.

Eye Irrit. 2 :Causes serious eye irritation.

STOT SE 3 :May cause drowsiness or dizziness.

Carc. 2 :Suspected of causing cancer.

#### 2.2 Label elements

According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567

Product Name NEOPAINT NPT16 - AEROSOL

Hazard Pictogram(s)



## NEOPAINT NPT16 - AEROSOL

	GHS08	GHS07
Signal Word(s)	Warning	
Hazard Statement(s)	H229: Pressurised container: May burst if heated. H315: Causes skin irritation. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. H351: Suspected of causing cancer.	
Precautionary Statement(s)	P201: Obtain special instructions before use. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251: Do not pierce or burn, even after use. P261: Avoid breathing mist/vapours/spray. P271: Use only outdoors or in a well-ventilated area. P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.	

### 2.3 Other hazards

None known.

### 2.4 Additional Information

For full text of H/P Statements see section 16.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product as supplied: Aerosol.

### 3.1 Substances

Not applicable.

### 3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / Registration number(s)	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Dichloromethane	75-09-2	200-838-9	60-70	Skin Irrit. 2 H315 Eye Irrit. 2 H319 STOT SE 3 H336 Carc. 2 H351	GHS08 GHS07
Carbon dioxide	124-38-9	204-696-9	10-20	Press. Gas (Comp.) H280	GHS04
Xylene	1330-20-7	215-535-7	1-10	Flam. Liq. 3 H226 Acute Tox. 4 H312 Skin Irrit. 2 H315 Acute Tox. 4 H332	GHS02 GHS07
Ethylbenzene	100-41-4	202-849-4	<2	Flam. Liq. 2 H225 Asp. Tox. 1 H304 Acute Tox. 4 H332 STOT RE 2 H373	GHS02 GHS08 GHS07

For full text of H/P Statements see section 16.

## NEOPAINT NPT16 - AEROSOL

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures

Inhalation	Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.
Skin Contact	Take off contaminated clothing and wash it before reuse. Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Wash out mouth with water. If symptoms persist, obtain medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness.  
Suspected of causing cancer.

#### 4.3 Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get medical advice/attention.

### SECTION 5: FIREFIGHTING MEASURES

Pressurised container: May burst if heated.

#### 5.1 Extinguishing media

Suitable Extinguishing media	As appropriate for surrounding fire.
Unsuitable extinguishing media	None known.

#### 5.2 Special hazards arising from the substance or mixture

Heating may cause pressure rise with risk of bursting. Decomposes in a fire giving off toxic fumes: Phosgene, Hydrogen chloride, Carbon monoxide, Carbon dioxide.

#### 5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions. Keep containers cool by spraying with water if exposed to fire.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

#### 6.1 Personal precautions, protective equipment and emergency procedures

Stop leak if safe to do so. Provide adequate ventilation. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Ensure full personal protection (including respiratory protection) during removal of spillages.

#### 6.2 Environmental precautions

Do not release large quantities into the surface water or into drains.

## NEOPAINT NPT16 - AEROSOL

### 6.3 Methods and material for containment and cleaning up

Collect mechanically and dispose of according to Section 13. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a lidded container for disposal or recovery. Containers must not be punctured or destroyed by burning, even when empty.

### 6.4 Reference to other sections

See Also Section 8, 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurised container - Do not pierce or burn, even after use. Provide adequate ventilation. Use only outdoors or in a well-ventilated area. Avoid breathing mist/vapours/spray. Avoid contact with skin and eyes. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands and exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Protect from sunlight. Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Storage temperature

Do not expose to temperatures exceeding 50°C/ 122°F.

Storage life

Stable under normal conditions.

Incompatible materials

Strong oxidising agents, Alkalies, Zinc, Aluminium.

### 7.3 Specific end use(s)

White Background Paint for use in the Magnetic Particle Inspection Process (BS EN ISO 9934-2:2002).

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### 8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTCL (8 hr TWA ppm)	LTCL (8 hr TWA mg/m <sup>3</sup> )	STEL (ppm)	STEL (mg/m <sup>3</sup> )	Note
Dichloromethane	75-09-2	100	353	200	706	BMGV, Sk
Carbon dioxide	124-38-9	5000	9150	15000	27400	
Xylene, o-,m-,p- or mixed isomers	1330-20-7	50	220	100	441	Sk, BMGV
Ethylbenzene	100-41-4	100	441	125	552	Sk

Region  
United Kingdom

Source  
UK Workplace Exposure Limits EH40/2005 (Fourth edition, published 2020)

Remark  
BMGV

Notes  
Biological monitoring guidance values are listed in Table 2.

Sk  
Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

## NEOPAINT NPT16 - AEROSOL

Biological Exposure Indices						
Substances	CAS Number	Sampling	Tissues	Control parameters	Biological monitoring guidance value	Comments
Dichloromethane	75-09-2	Post shift	end-tidal breath	carbon monoxide	30 ppm	
Xylene, o-, m-, p- or mixed isomers	1330-20-7	Post shift	urine	methyl hippuric acid	650 mmol methyl hippuric acid/mol creatinine	

### 8.2 Exposure controls

8.2.1. Appropriate engineering controls Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Use with ventilation, local exhaust ventilation or breathing protection. A washing facility/water for eye and skin cleaning purposes should be present.

#### 8.2.2. Personal protection equipment



Eye Protection

Wear eye protection with side protection (EN166).



Skin protection

Wear suitable protective clothing and gloves. Impervious gloves (EN 374).  
Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Protective gloves should be replaced at first signs of wear.  
Material: Fluorinated Rubber (Viton)  
Break through time: > 480 min  
Glove thickness: > 0.4 mm  
Material: PVA  
Break through time: > 480 min  
Glove thickness: > 0.4 mm  
Material: Butyl Rubber  
Break through time: > 10 min  
Glove thickness: > 0.4 mm



Respiratory protection

Wear a suitable respirator to keep the solvent vapour concentration below the occupational limit values. A suitable mask with filter type AX is appropriate.



Thermal hazards

Not applicable.

8.2.3. Environmental Exposure Controls Do not release large quantities into the surface water or into drains.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance Aerosol  
Colour: White.

## NEOPAINT NPT16 - AEROSOL

Odour	Characteristic odour.
Odour threshold	Not established.
pH	Not known.
Melting point/freezing point	-94.9°C (Dichloromethane)
Initial boiling point and boiling range	39.8°C (Dichloromethane)
Flash Point	Not applicable.
Evaporation rate	Not known.
Flammability (solid, gas)	Non-flammable.
Upper/lower flammability or explosive limits	Not known.
Vapour pressure	584 hPa (352 mm Hg) @ 25°C (Dichloromethane)
Vapour density	Not known.
Density (g/ml)	1.32 @ 25°C (Dichloromethane)
Relative density	Not known.
Solubility(ies)	Solubility (Water): Insoluble in water. Solubility (Other): Not known.
Partition coefficient: n-octanol/water	1.25 (Dichloromethane)
Auto-ignition temperature	Not known.
Decomposition Temperature (°C)	Not known.
Viscosity	Not known.
Explosive properties	Pressurised container: May burst if heated.
Oxidising properties	Not oxidising.
<b>9.2 Other information</b>	None.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

Stable under normal conditions.

### 10.2 Chemical Stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

### 10.4 Conditions to avoid

Keep away from heat and direct sunlight.

### 10.5 Incompatible materials

Strong oxidising agents, Alkalis, Zinc, Aluminium.

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Acute toxicity - Ingestion

Calculation method : Not classified.

Low oral toxicity.

Dichloromethane: LD50 (rat) > 2000 mg/kg

## NEOPAINT NPT16 - AEROSOL

Acute toxicity - Skin Contact	Calculation method : Not classified. Low acute toxicity. Dichloromethane: LD50 (rat) > 2000 mg/kg
Acute toxicity - Inhalation	Calculation method : Not classified. Low acute toxicity. Dichloromethane: LC50 (rat) (4 hours) = 49 mg/l
Skin corrosion/irritation	Calculation method : Causes skin irritation. No data.
Serious eye damage/irritation	Calculation method : Causes serious eye irritation. No data.
Skin sensitization data	Calculation method : Not classified. It is not a skin sensitiser.
Respiratory sensitization data	Calculation method : Not classified.
Germ cell mutagenicity	Calculation method : Not classified. There is no evidence of mutagenic potential.
Carcinogenicity	Calculation method : Suspected of causing cancer. No data. Dichloromethane: A3: Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histological type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiological studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure.
Reproductive toxicity	Calculation method : Not classified. No evidence of reproductive effects.
Lactation	Calculation method : Not classified.
STOT - single exposure	Calculation method : May cause drowsiness or dizziness. No data.
STOT - repeated exposure	Calculation method : Not classified.
Aspiration hazard	Calculation method : Not classified.
<b>11.2 Other information</b>	Not known.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

Toxicity - Aquatic invertebrates	Low toxicity to invertebrates.
Toxicity - Fish	Low toxicity to fish. Dichloromethane: LC50 (96 hour) = 193 mg/l
Toxicity - Algae	Low toxicity to algae.
Toxicity - Sediment Compartment	Not classified.
Toxicity - Terrestrial Compartment	Not classified.

### 12.2 Persistence and degradability

The product is biodegradable. The product is unlikely to persist in the environment.

### 12.3 Bioaccumulative potential

## NEOPAINT NPT16 - AEROSOL

The product has no potential for bioaccumulation.

Dichloromethane: Bioconcentration factor (BCF): 2.0-5.4

### 12.4 Mobility in soil

The product is volatile and will partition into the atmosphere. The product has high mobility in soil.

### 12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

### 12.6 Other adverse effects

Not known.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Non-emptied aerosol: Dispose of wastes in an approved waste disposal facility.

### 13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number

UN No. 1950

### 14.2 UN proper shipping name

UN proper shipping name AEROSOLS

### 14.3 Transport hazard class(es)

ADR/RID

ADR/RID Class 2

ADR Classification Code 5A

Special Provisions 190, 327, 344, 625

Limited Quantities 1 L

Excepted Quantities E0

Emergency Action Code

Mixed Packing Instructions for Packages P207 LP200

Special Packing Provisions for Packages PP87 RR6 L2

Mixed Packing Instructions for Packages MP9

Packing Instructions for Portable Tanks

Special Provisions for Portable Tanks



## NEOPAINT NPT16 - AEROSOL

Tank Code for Tanks

Special Provisions for Tanks

Vehicle for Tank Carriage

ADR Transport Category 3

Tunnel Restriction Code E

Special Provisions for Carriage - V14

Packages

Special Provisions for Carriage - Bulk

Special Provisions for Carriage - Loading, CV9 CV12

Unloading and Handling

Special Provisions for Carriage -

Operation

ADR HIN

IMDG

IMDG Class 2

Special Provisions 190, 327, 344, 625

Limited Quantities 1 L

Excepted Quantities E0

Mixed Packing Instructions for Packages P207 LP200

Special Packing Provisions for Packages PP87 RR6 L2

Packing Instructions for Portable Tanks

Special Provisions for Portable Tanks

IMDG EMS F-D, S-U

Stowage and Handling SW1 SW22

Segregation SG69

Marine Pollutant

ICAO/IATA

IATA Proper Shipping Name AEROSOLS

Excepted Quantities E0

Passenger and Cargo Aircraft Limited Y203

Quantities Packing Instructions

Passenger and Cargo Aircraft Limited 30Kg

Quantities Max net Qty

Passenger and Cargo Aircraft Packing 203

Instructions

Passenger and Cargo Aircraft Max net 75Kg

Qty

Cargo Aircraft Packing Instructions 203

Cargo Aircraft Max net Qty 150Kg

Special Provisions A98, A145, A167, A802

Emergency Response Guidebook (ERG) 2L

Code

Labels

Labels 2.2

## NEOPAINT NPT16 - AEROSOL



### 14.4 Packing group

Packing group

### 14.5 Environmental hazards

Environmental hazards Not classified as a Marine Pollutant.

### 14.6 Special precautions for user

Special precautions for user Not known.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

No information available

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

United Kingdom Regulations - Authorisations and/or Restrictions On Use

UK REACH Candidate List of Substances Not listed  
of Very High Concern for Authorisation

UK REACH Authorisation List (Annex XIV) list of substances subject to  
authorisation Not listed

UK REACH Restrictions List (Annex XVII) Dichloromethane (75-09-2), Xylene (1330-20-7), Ethylbenzene (100-41-4)  
Restrictions on the manufacture, placing  
on the market and use of certain  
dangerous substances, mixtures and  
articles

UK REACH Rolling Action Plan (RAP) Not listed  
The Persistent Organic Pollutants  
Regulations 2007 (SI 2007/3106) as  
amended Not listed

The Ozone-Depleting Substances and  
Fluorinated Greenhouse Gases  
(Amendment etc.) (EU Exit) Regulations  
2019 (SI 2019/583) Not listed

The Prior Informed Consent (PIC)  
Regulations concerning the export and  
import of hazardous chemicals  
SI2008/2108 as amended Not listed

European Regulations - Authorisations and/or Restrictions On Use

Community Rolling Action Plan (CoRAP) Dichloromethane (75-09-2), Xylene (1330-20-7)

### 15.2 Chemical Safety Assessment

United Kingdom Not applicable.

## SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

1-16

## NEOPAINT NPT16 - AEROSOL

### LEGEND

#### Hazard Pictogram(s)



GHS08



GHS07

#### Hazard classification

GHS02: GHS: Flame

GHS04: GHS: Gas cylinder

Flam. Liq. 2 : Flammable liquid, Category 2

Flam. Liq. 3 : Flammable liquid, Category 3

Aerosol 3 : Aerosol, Category 3

Press. Gas (Comp.) : Gases under pressure, Compressed gas

Asp. Tox. 1 : Aspiration hazard, Category 1

Acute Tox. 4 : Acute toxicity, Category 4

Skin Irrit. 2 : Skin corrosion/irritation, Category 2

Eye Irrit. 2 : Serious eye damage/irritation, Category 2

Acute Tox. 4 : Acute toxicity, Category 4

STOT SE 3 : Specific target organ toxicity — single exposure, Category 3

Carc. 2 : Carcinogenicity, Category 2

STOT RE 2 : Specific target organ toxicity — repeated exposure, Category 2

#### Hazard Statement(s)

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H280: Contains gas under pressure; may explode if heated.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

#### Precautionary Statement(s)

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251: Do not pierce or burn, even after use.

## NEOPAINT NPT16 - AEROSOL

P261: Avoid breathing mist/vapours/spray.

P264: Wash hands and exposed skin thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P312: Call a POISON CENTRE/doctor if you feel unwell.

P321: Specific treatment (see Medical Advice on this label).

P332+P313: If skin irritation occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

P501: Dispose of contents in accordance with local, state or national legislation.

ADN : European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE : Acute Toxicity Estimate

CAS : Chemical Abstracts Service

DNEL : Derived No Effect Level

EC : European Community

EINECS : European Inventory of Existing Commercial Chemical Substances

IATA : International Air Transport Association

IBC : Intermediate Bulk Container

ICAO : International Civil Aviation Organization

IMDG : International Maritime Dangerous Goods

LTEL : Long term exposure limit

PBT : Persistent, Bioaccumulative and Toxic

PNEC : Predicted No Effect Concentration

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STEL : Short term exposure limit

STOT : Specific Target Organ Toxicity

UN : United Nations

vPvB : very Persistent and very Bioaccumulative

### Acronyms

## NEOPAINT NPT16 - AEROSOL

Key literature references and sources for GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 data used to compile the SDS

### Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose.

Johnson and Allen Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Johnson and Allen Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.