



## JAC 3 - AEROSOL SAFETY DATA SHEET

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

### 1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

<b>1.1 Product identifier</b>	Product Name	JAC 3 - AEROSOL.
	CAS No.	Mixture.
	EINECS No.	Mixture.
	REACH Registration No.	None assigned.
<b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b>	Identified use(s)	<ul style="list-style-type: none"> <li>• Quick drying cleaner and de-greaser. Suitable for use in the Dye Penetrant Inspection Process BS EN ISO 571-1 (BS EN ISO 3452-2 Sensitivity Level 2 when used in conjunction with penetrant family products).</li> <li>• Surface coating.</li> </ul>
	Uses advised against	None known.
<b>1.3 Details of the supplier of the Safety Data Sheet</b>	Company Identification	Johnson and Allen Ltd Neocol Works Smithfield Sheffield S3 7AR. 0114 2738066 0114 2729842 info@johnsonandallen.co.uk
	Telephone	
	Fax	
	E-Mail (competent person)	
<b>1.4 Emergency telephone number</b>	Emergency Phone No.	0114 2738066. (UK office hours 08.30-17.00)

### 2. SECTION 2: HAZARDS IDENTIFICATION

<b>2.1 Classification of the substance or mixture</b>	<b>Regulation (EC) No. 1272/2008 (CLP)</b>	Aerosol 1; Extremely flammable aerosol. Pressurised container: May burst if heated. Eye Irrit. 2; Causes serious eye irritation. STOT SE 3; May cause drowsiness or dizziness.
<b>2.2 Label elements</b>	Product Name	According to Regulation (EC) No. 1272/2008 (CLP) JAC 3 - AEROSOL.
	Hazard Pictogram	 
		GHS02      GHS07
	Signal word(s)	Danger.
	Hazard statement(s)	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.

## JAC 3 - AEROSOL

Precautionary statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P261: Avoid breathing vapours.  
 P280: Wear protective gloves/eye protection/face protection.  
 P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.  
 Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep out of the reach of children.

Additional Information

**2.3 Other hazards**

Repeated exposure may cause skin dryness or cracking.

**2.4 Additional Information**

For full text of H/P Statements see section 16.

### 3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product as supplied: Aerosol.

**3.1 Substances**

Not applicable.

**3.2 Mixtures**

EC Classification No. 1272/2008

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard pictogram(s) and Hazard statement(s)
Dimethyl Ether	50-100	115-10-6	204-065-8	01-2119472128-37-0000	GHS02, Flam. Gas 1; H220, GHS04, Press. Gas; H280
Acetone	25-50	67-64-1	200-662-2	01-2119471330-49-0000	GHS02, Flam. Liq. 2; H225, GHS07, Eye Irrit. 2; H319, STOT SE 3; H336, EUH066

**3.3 Additional Information**

For full text of H/P Statements see section 16.

### 4. SECTION 4: FIRST AID MEASURES



**4.1 Description of first aid measures**

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact

Wash skin with soap and water. If symptoms persist, obtain medical attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

## JAC 3 - AEROSOL

Ingestion	Wash out mouth with water. If symptoms persist, obtain medical attention.
<b>4.2 Most important symptoms and effects, both acute and delayed</b>	Eye Contact: Irritation, Pain. Skin Contact: Repeated exposure may cause skin dryness or cracking.
<b>4.3 Indication of any immediate medical attention and special treatment needed</b>	Inhalation: May cause drowsiness or dizziness. Unlikely to be required but if necessary treat symptomatically.

### 5. SECTION 5: FIRE-FIGHTING MEASURES

Extremely flammable aerosol. Pressurised container: May burst if heated.

<b>5.1 Extinguishing Media</b>	
Suitable Extinguishing Media	Extinguish with waterspray, dry chemical, sand or carbon dioxide.
Unsuitable Extinguishing Media	Water jet spray.
<b>5.2 Special hazards arising from the substance or mixture</b>	Heating may cause pressure rise with risk of bursting.
<b>5.3 Advice for fire-fighters</b>	Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions. Keep containers cool by spraying with water if exposed to fire.

### 6. SECTION 6: ACCIDENTAL RELEASE MEASURES

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

<b>6.1 Personal precautions, protective equipment and emergency procedures</b>	Ensure adequate ventilation. Eliminate all ignition sources if safe to do so. Avoid breathing vapours. Avoid contact with eyes. Wear protective gloves/eye protection. Wash hands thoroughly after handling.
<b>6.2 Environmental precautions</b>	Do not release large quantities into the surface water or into drains.
<b>6.3 Methods and material for containment and cleaning up</b>	Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a lidded container for disposal or recovery. Containers must not be punctured or destroyed by burning, even when empty.
<b>6.4 Reference to other sections</b>	See Also Section 8 and 13.

### 7. SECTION 7: HANDLING AND STORAGE

<b>7.1 Precautions for safe handling</b>	Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid contact with eyes. Avoid inhalation of high concentrations of vapours. Avoid prolonged skin contact. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling.
--	---

## JAC 3 - AEROSOL

- 7.2 Conditions for safe storage, including any incompatibilities**
- Storage Temperature: Store locked up. Protect from sunlight. Store in a well-ventilated place.
- Storage Life: Ambient. Do not expose to temperatures exceeding 50°C/122°F.
- Incompatible materials: Stable under normal conditions.
- 7.3 Specific end use(s)**
- None known.
  - Quick drying cleaner and de-greaser. Suitable for use in the Dye Penetrant Inspection Process BS EN ISO 571-1 (BS EN ISO 3452-2 Sensitivity Level 2 when used in conjunction with penetrant family products).
  - Surface coating.

## 8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### 8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m <sup>3</sup> )	STEL (ppm)	STEL (mg/m <sup>3</sup> )	Note
Dimethyl Ether	115-10-6	400	766	500	958	WEL
Acetone	67-64-1	500	1210	1500	3620	WEL

WEL: Workplace Exposure Limit (UK HSE EH40)

#### 8.1.2 Biological limit value

Not established.

#### 8.1.3 PNECs and DNELs

Not established.

### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Provide adequate ventilation. A washing facility/water for eye and skin cleaning purposes should be present.

#### 8.2.2 Personal protection equipment

Eye/face protection



Wear suitable eye/face protection.

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely.

Respiratory protection



In case of insufficient ventilation, wear suitable respiratory equipment. A suitable mask with filter type AX may be appropriate.

Thermal hazards

Not applicable.

#### 8.2.3 Environmental Exposure Controls

Do not release large quantities into the surface water or into drains.

## JAC 3 - AEROSOL

### 9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Colourless.
Odour	Characteristic.
Odour Threshold	Not available.
pH	Not applicable.
Melting Point/Freezing Point	Not applicable.
Initial boiling point and boiling range	-24 °C
Flash point	-42 °C
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	2.6 – 18.6 Vol-%
Vapour pressure	5200 hPa @ 20 °C
Vapour density	Not available.
Relative density	0.732 g/cm <sup>3</sup> @ 20 °C
Solubility(ies)	Immiscible with water.
Partition coefficient: n-octanol/water	Not applicable.
Auto-ignition temperature	Product is not selfigniting.
Ignition temperature	235 °C
Decomposition Temperature	Not available.
Kinematic Viscosity	Not applicable.
Explosive properties	Pressurised container: May burst if heated.
Oxidising properties	No information available.

#### 9.2 Other information

Solvent content: Organic solvents	94.0 %
Solid content	6.0 %

### 10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	Stable under normal conditions.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	No hazardous reactions known if used for its intended purpose.
10.4 Conditions to avoid	Keep away from heat, sources of ignition and direct sunlight.
10.5 Incompatible materials	None known.
10.6 Hazardous Decomposition Product(s)	No hazardous decomposition products known.

### 11. SECTION 11: TOXICOLOGICAL INFORMATION

Unlikely to cause harmful effects under normal conditions of handling and use.

#### 11.1 Information on toxicological effects

##### 11.1.1 Mixtures

##### Acute toxicity

Ingestion	Low oral toxicity.
Inhalation	STOT SE 3; May cause drowsiness or dizziness.
Irritation	Eye Irrit. 2; Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.

##### Corrosivity

Not classified.

##### Sensitisation

Not expected to be a skin or respiratory sensitiser.

##### Repeated dose toxicity

None anticipated.

##### Carcinogenicity

No evidence of carcinogenicity.

##### Mutagenicity

There is no evidence of mutagenic potential.

##### Toxicity for reproduction

None anticipated.

## JAC 3 - AEROSOL

11.2	<b>Aspiration hazard</b>	None anticipated.
	<b>Other information</b>	None.

### 12. SECTION 12: ECOLOGICAL INFORMATION

12.1	<b>Toxicity</b>	Low toxicity to aquatic organisms.
12.2	<b>Persistence and degradability</b>	Part of the components are poorly biodegradable. Dimethyl ether: 5% (28days) (OECD 301D)
12.3	<b>Bioaccumulative potential</b>	No information available.
12.4	<b>Mobility in soil</b>	Immiscible with water. The product is predicted to have low mobility in soil. The product is volatile and will partition into the atmosphere.
12.5	<b>Results of PBT and vPvB assessment</b>	Not classified as PBT or vPvB.
12.6	<b>Other adverse effects</b>	None.

### 13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1	<b>Waste treatment methods</b>	Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Non-emptied aerosol: Dispose of wastes in an approved waste disposal facility. Refer to manufacturer for information on recovery/recycling. Do NOT landfill.
13.2	<b>Additional Information</b>	Disposal should be in accordance with local, state or national legislation.

### 14. SECTION 14: TRANSPORT INFORMATION

14.1	<b>UN number</b>	UN 1950
14.2	<b>UN Proper Shipping Name</b>	AEROSOLS, Flammable.
14.3	<b>Transport hazard class(es)</b>	2.1
14.4	<b>Packing Group</b>	None.
14.5	<b>Environmental hazards</b>	Not classified as a Marine Pollutant.
14.6	<b>Special precautions for user</b>	None.
14.7	<b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
14.8	<b>Additional Information</b>	
	ADR Classification Code	5F
	IMDG Code	EmS: F-D, S-U
	Tunnel Restriction Code	D

### 15. SECTION 15: REGULATORY INFORMATION

15.1	<b>Safety, health and environmental regulations/legislation specific for the substance or mixture</b>	
15.1.1	<b>EU regulations</b>	
	<b>Authorisations and/or restrictions on use</b>	
	Candidate List of Substances of Very High Concern for Authorisation	All chemicals are not listed.
	REACH: ANNEX XVII Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	All chemicals are not listed.
	REACH: ANNEX XIV List of substances subject to authorisation	All chemicals are not listed.
	Community Rolling Action Plan (CoRAP)	All chemicals are not listed.
15.1.2	<b>National regulations</b>	None known.
15.2	<b>Chemical Safety Assessment</b>	Not applicable.

## JAC 3 - AEROSOL

### 16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 14

#### LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative
Flam. Gas 1	Flammable gas Category 1
Aerosol 1	Flammable aerosol Category 1
Flam. Liq. 2	Flammable liquid Category 2
Press. Gas	Gases under pressure
Eye Irrit. 2	Serious eye damage/irritation Category 2
STOT SE 3	Specific target organ toxicity — single exposure Category 3

#### Hazard statement(s) and Precautionary statement(s)

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
P251	Pressurized container: Do not pierce or burn, even after use.
P261	Avoid breathing vapours.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

#### Hazard pictogram(s)

GHS02



GHS07



GHS04



## JAC 3 - AEROSOL

### **Disclaimers**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose.

Johnson and Allen Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law.

Johnson and Allen Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

### **Annex to the extended Safety Data Sheet (eSDS)**

Not applicable.